



E-scape.

OMNI VERGE

UNIVERSAL DRY VERGE SYSTEM



PRODUCT DESCRIPTION

A universal, mortar-free dry verge system manufactured from durable UV-stable polypropylene. The non-handed design fits both the left and right sides of a gable, simplifying stockholding and installation. Suitable for roof pitches from 15° to 55° and batten gauges from 270mm to 345mm, the system provides a neat, secure and low-maintenance finish to the roof verge.

USE

- Pitched-roof verge applications on new-build and refurbishment projects.
- Left- or right-hand gable ends using the same non-handed component.
- Most interlocking clay and concrete roof tiles.
- Roof pitches from 15° to 55°.

FEATURES & BENEFITS

- Universal non-handed design fits either side of the roof.
- Mortar-free system gives a clean, consistent finished appearance.
- Fast fitting - designed to allow up to 36 verge units to be installed in under 5 minutes.
- Mechanically fixed through pre-drilled holes for a secure installation.
- UV-stable polypropylene provides durable long-term external performance.
- Four colour options help coordinate with common roof finishes.

QUALITY & STANDARDS

- Conformity to BS 5534: Code of Practice for Slating & Tiling for Pitched Roofs & Vertical Tiling.
- Conformity to BS 8612: Dry Fixed Ridge, Hip & Verge Systems for Slating & Tiling.

Roof pitch: 15° to 55°

Batten gauge: 270mm to 345mm

Material: UV-stable polypropylene

Colours: Grey, Brown, Terracotta and Black

Tile compatibility: Most interlocking clay and concrete tiles

Unit weight: 0.20kg per verge unit

Approx. dimensions: 410mm (L) x 164mm (H); 150mm interlocking section; profile 160/129/50mm (widest) and 137/102mm (narrowest)

Fixing: Mechanical fixing into tiling battens

MATERIAL

- UV-stable polypropylene.
- Available colours: Grey, Brown, Terracotta and Black.

INSTALLATION ADVICE

- Install in accordance with the E-Scape installation guidance.
- Position the verge unit to engage securely with the roof tile profile and tiling batten.
- Mechanically fix through the pre-drilled fixing holes into the tiling battens using suitable ring shank nails.
- Maintain a batten gauge between 270mm and 345mm.
- Use only with compatible interlocking clay and concrete tiles.
- Not suitable for slates or high-profile roof tiles.

COMPONENT	MATERIAL	UNIT WEIGHT	COLOUR OPTIONS	FUNCTION/FIXING
Verge Unit	UV-stable polypropylene	0.20kg	Grey / Brown / Terracotta / Black	Universal left/right unit, mechanically fixed to tiling batten

BOX QUANTITY	BOX DIMENSIONS	BOX WEIGHT
50	591 x 462 x 423mm	10.5kg

Also available - Ridge End Caps & Starter/End Packs. For best results, use in conjunction with our compatible ridge end caps, available for both angled and half-round ridge tiles, and dedicated starter plates and closing units for a secure, professional verge finish.