



RIDGE KIT



DESCRIPTION

The E-Scape Dry-Fix Ridge kit provides an efficient roofing solution using a breathable ridge roll that covers the roof batten with strong fixings to secure the Ridge tiles into place. Our Ridge roll is constructed from a polypropylene hydrophobic mesh, allowing for ventilation while also acting as a water-repellent barrier. To ensure secure adhesion to the tile or slate, the roll is equipped with a butyl strip for effective installation. We would recommend the area is clean and dry, to maximise the butyl's strength.

PRODUCT FEATURES

The E-Scape Ridge roll provides the recommended 5mm continuous ventilation through its corrugated aluminium. Our Ratchet clips feature extensive teeth for superior strength, ensuring quick installation. The unions are flexible yet maintain their integrity when flexed. Additionally, the incorporated tracks effectively divert rainfall away from the ridge line.

BRITISH STANDARDS

Complies with BS 5534

Code of Practice for Slating & Tiling for Pitched Roofs & Vertical Tiling.

Complies with BS 8612

Dry Fixed Ridge, Hip & Verge Systems for Slating & Tiling.

COMPATABILITY

Compatible with:

- Slates
- Concrete Ridge Tiles
- Half-Round & Angled Ridge tiles
- Pitched roof angles between 15 and 45 degrees

KIT CONTENTS & MATERIALS

Ridge roll (1)

Polypropylene hydrophobic mesh, corrugated aluminium and butyl self adhesive strip

Unions (13)

Film grade polypropylene

Centre Ratchet Clips (13)

Glass filled Nylon

Outer Ratchet Clips (26)

Polypropylene

Batten Straps (10)

Stainless Steel

Screws (13)

Stainless Steel

15-year warranty on components only if installed in accordance with BS 5534 & BS 8612

